

RENE'E

Decorative paint with 3D Glitter Effects

Type of Product

An acrylic, water based paint for interior with proprietary 3D glitter technology.

Use and Characteristics

A glittery sparkle gives RENE'E its eccentric and elegant texture. Inspired from the sparkly 80's full of colours and light, RENE'E is a water based decorative paint for interiors with its refined effects.

Technical Specifications

◆ Specific Gravity (ISO 2811) :	1.05 ± 0.05 kg/l
◆ Viscosity @ 23 °C (ISO 2884) :	8.000 ± 1.000 cP (R5 RPM20 a 23°C)
◆ Dry Residue:	33 ± 2 %
◆ Tested pH:	8,5 ± 0,2
◆ Drying Time (a 20 °C ed U.R. del 60%):	4 to 6 hrs, depending on room conditions
◆ Washability:	RENEE is washable with a soft moist cloth and little pressure for regular maintenance.
◆ Resistance to U.V. rays:	resistant, non-yellowing

Information for Application

Theoretical Coverage:	10 – 12 m ² /L
N° of Coats:	2
Application:	Large ceiling brush
Dilution:	10-20 % max.
Type of diluent:	potable water

Surfaces

All surface are adequate from stucco to wallboard. All surfaces flat and smooth.

Application Cycle

The application cycle for RENE'E is the following:

- FASHION PRIMER FINE - acrylic water based primer
- RENE'E – Decorative finish in two coats.

Surface Preparation and Application

- **Suitable surfaces**
All plain and smooth surfaces, stucco or wallboard.
- **Preparation of the surface**
After stuccoing apply one or two coats of FASHION FIX diluted 1:3 with water using a paint brush.
- **Application of FASHION PRIMER FINE**
After having adequately prepared the surface, apply one or two coats of FASHION PRIMER SABBIATO "Per VENUS" using a short hair roller (art. 490.20). In case of very porous walls apply a third coat diluted with 30-40% water.
- **Application of RENE'E**
After 24 hours from the application of FASHION PRIMER FINE, in the same colour as the final coat, can be applied in the first coat diluted by 10%. Apply with a brush. If the product is too thick when applying dilute further up to a maximum of 20% from the original container. Apply in large brush strokes but homogeneous. Check the overall effect when dry and if a greater glittering effect is desired apply a second coat after 5 to 6 hours of the first coat.
- **PREPARATION OF COLORS**
To obtain the colors presented on the ECLA colour charts use the ECLA product FASHION COLOUR as indicated by the directions and mix well.
Dosage different from the one indicated will yield different shades than the ones presented.

How to Apply/ use

Dip the paint instrument in RENE'E (diluted as required) and apply one or two coats as desired on the surface already prepared with FASHION PRIMER FINE in a compact and homogeneous way avoiding squaring.

Packaging

1 L – 5 L

Warnings

It is recommended to apply the product on surfaces with temperatures above +5 °C and below +35 °C and with ambient humidity levels <85%.
Clean utensils with water after use.

Storage

Store the product in its original containers with the inner and outer seal at temperatures between +5°C and +40°C, away from direct sunlight. Prevent product from freezing. Product shelf life is of 12 months if the above conditions are met.

Health, Safety & Environment

The product does not require any special labelling according to current CEE norms. However, it is recommended to follow normal HSE practices and applicable local norms for safety in the handling, storage and disposal of this product.

Recommended disposal of product = Allow product to dry then dispose of residue as special material. Follow local norms for disposal.



[www.ecladecoration.it/mail:info\(a\)eladecoration.com](http://www.ecladecoration.it/mail:info(a)eladecoration.com)

Rev. 02 – Settembre 2013

I valori indicati in questa scheda sono frutto di prove di laboratorio e prove pratiche e quindi sono suscettibili di modifiche che possono essere apportate a fronte di nuove esperienze e della continua ricerca. Quanto indicato circa i modi di impiego ed i risultati ottenibili con il nostro prodotto, corrisponde alle nostre concrete esperienze senza tuttavia costituire impegno e responsabilità. Pertanto la vendita del prodotto non è coperta da garanzie per quanto riguarda l'applicazione e viene effettuata con l'intesa che l'utilizzatore ne determinerà l'idoneità per le sue applicazioni.