

CHER

Transparent Finish with Glitter effects

Type of Product

Transparent water based clear coat for interior with refined glittering 3D effects.

Application and Characteristics

CHER, is a transparent water based clear coat (vitrescent) for interiors with 3D glitter that is applied to any surface and yields a luxurious brilliant finish when applied to all paints and decorative finishes.

Physical Characteristics

◆	Specific Gravity (ISO 2811) :	1,05 kg/l
◆	Viscosity @ 23 °C (ISO 2884) :	400 mPa
◆	Dry Residue:	42,0%
◆	Tested pH:	8,5
◆	Drying time (@ 20 °C & R.H. 60%):	from 4 to 6 hrs, but varies with room conditions
◆	Washability:	CHER is resistant to light maintenance using a damp soft cloth.
◆	Resistance to U.V. rays:	resistant, non-yellowing

Information for Application

Theoretical coverage :	15– 18 m ² /L
Recommended coats:	1
Application:	Ceiling brush, large brush with soft bristle
Dilution:	none required
Type of diluent:	potable water, if required

Surfaces

All surface are adequate from stucco to wallboard. All surfaces flat and smooth.

Application Cycle

The application cycle of **CHER** is a single application step consisting in:

- **CHER** – Clear coat with glitter effects

Surface Preparation and Application

- **Suitable surfaces**
All plain and smooth surfaces, stucco or wallboard.
- **Application of CHER**
Apply one or two coats of CHER on any type of painted surface (either regular or decorative paint) using a large broad brush..

How to Apply / Use

Dip the paint brush into the container and apply CHER in a single coat. Apply using large brush strokes maintaining an even application without squaring effects.

Apply a second coat if a more brilliant effect is desired. Allow proper drying time between coats.

Packaging

1 L

Warnings

It is recommended to apply the product on surfaces with temperatures above +5 °C and below +35 °C and with ambient humidity levels <85%.

Storage

Store the product in its original containers with the inner and outer seal at temperatures between +5°C and +40°C, away from direct sunlight. Prevent product from freezing.

Product shelf life is of 12 months if the above conditions are met.

Health, Safety & Environment

The product does not require any special labelling according to current CEE norms. However, it is recommended to follow normal HSE practices and applicable local norms for safety in the handling, storage and disposal of this product.

Recommended disposal of product = Allow product to dry then dispose of residue as special material. Follow local norms for disposal.



[www.ecladecoration.it/mail:info\(a\)eladecoration.com](http://www.ecladecoration.it/mail:info(a)eladecoration.com)

Rev. 02 – Settembre 2013

I valori indicati in questa scheda sono frutto di prove di laboratorio e prove pratiche e quindi sono suscettibili di modifiche che possono essere apportate a fronte di nuove esperienze e della continua ricerca. Quanto indicato circa i modi di impiego ed i risultati ottenibili con il nostro prodotto, corrisponde alle nostre concrete esperienze senza tuttavia costituire impegno e responsabilità. Pertanto la vendita del prodotto non è coperta da garanzie per quanto riguarda l'applicazione e viene effettuata con l'intesa che l'utilizzatore ne determinerà l'idoneità per le sue applicazioni.